

# SWISHER ZERO-TURN MOWERS

Model #	Swisher ZT2450A	Ride King ZT2452	Swisher ZT2454	Z-Max ZT2660B	Big Mow ZT2766	Pro-Series ZT2766KP
Deck Size	50"	52"	54"	60"	66"	66" (60" deck also available)
Engine	 24 HP Briggs & Stratton ELS V-Twin OHV	24 HP Briggs & Stratton ELS V-Twin OHV	24 HP Briggs & Stratton ELS V-Twin OHV	26 HP Briggs & Stratton ELS V-Twin OHV	27 HP Briggs & Stratton ELS V-Twin OHV	27 HP Kohler Courage V-Twin
Transmission	Dual Eaton commercial grade hydrostatic	Dual Eaton commercial grade hydrostatic	Dual Eaton commercial grade hydrostatic	Dual Eaton commercial grade hydrostatic	Dual Eaton commercial grade hydrostatic	Dual Eaton commercial grade hydrostatic
Warranty	Three-year limited transmission, two-year limited bumper-to-bumper/engine, one-year limited commercial	Three-year limited transmission, two-year limited bumper-to-bumper/engine, one-year limited commercial	Three-year limited transmission, two-year limited bumper-to-bumper/engine, one-year limited commercial	Three-year limited transmission, two-year limited bumper-to-bumper/engine, one-year limited commercial	Three-year limited transmission, two-year limited bumper-to-bumper/engine, one-year limited commercial	Three-year limited transmission, two-year limited bumper-to-bumper/engine, one-year limited commercial
Seat	Mid-back high seat	Mid-back high seat	Mid-back high seat	16" deluxe high-back	16" deluxe high-back	Deluxe high-back, weight adjustable, full suspension, lumbar support
Deck	11-gauge fabricated and welded steel	11-gauge stamped commercial style steel	11-gauge fabricated and welded steel	11-gauge fabricated and welded steel	11-gauge fabricated and welded steel	7-gauge fabricated and welded steel
Blades	Three commercial quality Gator Mulcher™ blades	Three commercial quality Gator Mulcher™ blades	Three commercial quality Gator Mulcher™ blades	Three commercial quality Gator Mulcher™ blades	Three commercial quality Gator Mulcher™ blades	Three commercial quality Gator Mulcher™ blades
Cutting Height Range	1.5" to 5"	1.5" to 5"	1.5" to 5"	1.5" to 5"	1.5" to 5"	1.5" to 5.5"
Cutting Height Adjustments	8	8	8	8	8	Unlimited within range
Deck lift	Handle/lever spring assisted	Handle/lever spring assisted	Handle/lever spring assisted	Handle/lever spring assisted	Handle/lever spring assisted	Electric actuator
Discharge chute	Molded plastic	Molded plastic	Molded plastic	Fabricated steel	Fabricated steel	Flexible rubber
Tires	Front- 4.1 x 3.5 x 5 Back- 18 x 9.5 x 8	Front- 4.1 x 3.5 x 5 Back- 18 x 9.5 x 8	Front- 4.1 x 3.5 x 5 Back- 18 x 9.5 x 8	Front- 4.1 x 3.5 x 5 Back- 20 x 10 x 8	Front- 4.1 x 3.5 x 5 Back- 20 x 10 x 8	Front- 13 x 6.5 x 6 Back- 23 x 10.5 x 12
Fuel capacity	4 gallons	4 gallons	4 gallons	4 gallons	4 gallons	12 gallons
Speed	6mph forward/6mph reverse	6mph forward/6mph reverse	6mph forward/6mph reverse	6mph forward/6mph reverse	6mph forward/6mph reverse	8.5mph forward/4mph reverse